



# ELASTO PRIMER

## Description

A 100% acrylic elastomeric primer coating for various uses on different types of roof and wall including rusted metal, asphalt, concrete and stucco. Excellent coating for above grade rust protection.

## Uses

Concrete, G.I Roof Metal, Asphalt, Wood.

## Features

- Reduces thermal cycling.
- Contains strong rust inhibitive pigments.
- Helps cool the surface.
- Prevents premature aging and leaks on roofing.
- Contains a strong mildewcide/fungicide.
- Excellent adhesion to various metal substrates.
- Easy to use, easy clean up, non-toxic.
- VOC compliant water based coating.
- Anti-efflorescence.

## Technical Data

<b>Color:</b>	White.
<b>Viscosity:</b>	Min. 115-120 KU @ 25°C/77°F
<b>Density:</b>	11.78 lbs./gal. ( ± 10%)
<b>Permeability:</b>	5 perms/inch. 20 mils thick coating.
<b>PH:</b>	>8.0 ± .5
<b>Percent Solids by Volume:</b>	45% ± 2%
<b>Percent Solids by Weight:</b>	51% ± 1%
<b>Flash Point:</b>	Same as water.
<b>Tensile Strength at Max Stress:</b>	100 lb/in <sup>2</sup>
<b>% Elongation at Break:</b>	250%-300% @ 25°C/77°F
<b>Fungi Resistance:</b>	Zero Growth
<b>Coverage:</b>	2 gallons per 100 sq. ft. Yields 20 dry mils. 3 gallons per 100 sq. ft. Yields 30 dry mils.
<b>Recommended Coverage:</b>	Two coats (20 mils) on new surface. Three coats (30 mils) on aged older surface.
<b>Min. Surface Application Temp.</b>	7.2°C/45°F. Do not allow to freeze.
<b>Drying Time:</b>	3 hrs. @ 25°C/77°F, 50% relative humidity.
<b>Packaging:</b>	4 gallon buckets, 50 gallon drums.

Elasto Coating System